

Description

1K brushable seam sealer. After curing builds a strong elastic layer with excellent sealing performance.

Features & Benefits

- overpaintable (with solvent and water based paints)
- resistant to water, oil, gasoline etc.
- quick drying

Substrate preparation

Clean, dry, and degrease the surface with a suitable anti-silicone cleaner. Pretreat metal surfaces with anti-corrosion primer, let dry and apply sealant.

Application data



Application

1 coat

Application temperature

With a brush along the seam

+15 °C to +35°C

(+59 °F to +95 °F)



Drying

Overpaintable (25 °C/77 °F), 1 mm thickness)

Skin time (20 °C/68 °F)

24 h

3 – 4 min

Prod. Nr.	Description	Weight	Packaging Box
1410-0,85	Grey	0,85 Kg	12

VOC

2004/42/ IIB(e) (840) 348

Shelf life

Min. 18 months from the production date under normal storage conditions between 15 °C/59 °F and 30 °C/86 °F and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.