

## 3002 Proseal High Temperature Silicone Sealant

Ver.: 2020-1

### Description

Permanently elastic, high quality black coloured silicone sealant with outstanding sealing and adhesion properties. It is recommended as sealing or adhesion mastic by assembling various motor or car body parts.



### Features & Benefits

- good adhesion on many substrates
- resistant to low (down to -65 °C/- 85 °F) as well as high temperatures (up to 230 °C/446 °F)
- resistant to vibrations, excellent chemical resistance (oils, hydraulic and cooling fluids, acids...)
- suitable for sealing of car lights, sumps, motor covers etc.

### Substrate preparation

Surfaces to be treated must be clean, dry and grease-free. Old sealing materials have to be removed from the surface completely.

### Application data

	<b>Mixing ratio</b>
	The product is ready to use!
	<b>Application</b>
	The product must be applied directly from the packaging immediately at the temperature range between 5 °C/41 °F and 35 °C/95 °F.
	Due to the broad application spectrum pre-testing is recommended.
	<b>Drying time</b>
	Skin formation time: approx 8 min (at 23 °C/73,4 °F) and 50 % r. a.h.)
	Full curing speed: approx 2-3 mm / 24 h
	Curing speed depends on temperature, relative air humidity and thickness.

## 3002 Proseal High Temperature Silicone Sealant

Ver.: 2020-1

Prod. Nr.	Description	Volume	Packaging Box
3002-0,2	Black	200 ml	12

### Shelf life

Min. 12 months from the production date under normal storage conditions at temperature between 5°C and 25°C and unopened cartridge.

### Additional Information

#### FOR PROFESSIONAL USE ONLY!

Always read the instructions.

**IMPORTANT:** This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.