

Description

Highly effective professional diesel particulate filter (DPF/FAP) cleaner. Effectively removes ash deposits without disassembly or removal of diesel particulate filter and significantly prolongs its service life.

Features & Benefits

- effective cleaning capabilities
- fast-acting
- non-corrosive
- prolongs the service life of the filter
- reduces risk of filter clogging
- reduces fuel consumption

Usage

- Shake well before use. Use the extension tube and apply the spray before the diesel particle filter, looking downstream of the exhaust system.
- Usually it is applied through the exhaust temperature sensor or exhaust pressure sensor opening hole.
- Temperature of the diesel particle filter should be under 40°C.
- It is recommended to apply five short sprays with duration around two seconds and wait about five seconds between each spray.
- After application install temperature or pressure sensor. Run the engine at idle power for around 15 minutes. Steam coming from the exhaust at the back of the car may be visible.
- Perform test drive (recommended duration of the test drive is 30 minutes). Try to keep engine RPMs between 1800 and 2500. It can also be used in case of service regeneration.

| Prod. Nr. | Description | Volume | Packaging per Pallet |
|-----------|-------------|--------|----------------------|
| 5650-0,4 | / | 400 mL | 1008 pcs |

Shelf life

Max. 18 months from the production date under normal storage conditions (+5°C to +40°C) and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfill the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results, or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.