

Product Information

6090 B9 Multi-Azure

High Performance Semi-Lightweight Putty

silco[®]
AUTOMOTIVE

Excellent

SANDING

*beginning with
P180 grit*

Better

**SURFACE
ASSESSMENT**

after sanding



Sanding

AFTER 20 MINUTES

*without paper
clogging*

Very easy

TO SPREAD

Rhapsody in blue for every Bodyshop.



6090 B9 Multi-Azure

High Performance Semi-Lightweight Putty

DRYING TIME *

Dry to sand
(20°C / 68 F) 20 min

Potlife
(20°C / 68 F) 3 - 4 min

**Indicative times subject to amount of hardener/application/environment.*

How to

APPLICATION

Treated surface must be clean, dry, rust-free and grease-free. Optimal adhesion can be achieved on well abraded surface. Mix the putty and hardener thoroughly until the colour is even. Use filler knife, plastic or rubber spatula for the application. Do not overdose! Excessive quantity of hardener can cause colour change on the topcoat and shorten the potlife. Hardener quantities below 2% can result in prolonged drying time.

For further and updated information please refer to the TDS published on www.silco.si.

Info

PRODUCT

High performance semi-lightweight polyester putty can be used as filling or finishing putty. Blue colour enables better surface assessment after sanding due to perfect colour contrast between sanded and unsanded putty. It is easy to apply and to sand with fine-grained sanding papers, beginning P180 or P240. Sanding after 20 minutes from application is easy and without any paper clogging.

Packaging

PUTTY & HARDENER

6090 B9 Multi-Azure

High Performance Semi-Lightweight Putty

Prod. Nr.	Content	Color
6090-1	1 L	Azure
BPO Hardener 2-3%	50 g	Red paste