

Description

90.655 Unimix Orientation Additive is an additive for mixed topcoats with a higher proportion of aluminum pigments (eg. RAL 9006). By using the additive, we improve the distribution and orientation of aluminum crystals, thus eliminating the cloudiness of the painted surface.

Features

- elimination of cloudiness of the painted surface
- easy dosing in mixed topcoat
- does not affect the basic properties of the coating

Use of additive


90.655 Orientation Additive is suitable for use in combination with the following Unimix binders: 90.300; 90.310; 90.320; 90.330; 90.510; 90.520; 90.530; 90.900; 90.910; 90.920; 90.930

Surface preparation



All surfaces must be properly prepared according to the instructions for preparing the surface for the mixed topcoat used.

Mixing ratio



Add 10 - 15 % in mixed topcoat. For the mixing ratio of mixed topcoat, hardener and thinner, see the technical data sheet for each mixed topcoat or binder.

Health and safety

For Health, Safety and Environmental instructions please refer to relevant Safety Data Sheets and labels on the cans. Storage conditions should also be considered.

Article no.	Description	Volume	Packaging
90.655	UniMix Orientation Additive	3 kg	/

Additional information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.