

Description

1K special structured coating for plastic body parts.


Features & Benefits

- direct application (without primer)
- quick drying
- good coverage
- structure regulation with spraying distance

Substrate preparation

Surfaces to be treated must be clean, dry and grease-free.

Application data



The product is ready to use!
Shake can thoroughly until the mixing balls move freely.



Number of coats 2 – 3
(regulate the structure with number of layers and spraying distance)

Spraying distance: 20 – 30 cm

Flash-off: 1 – 2 min

After spraying, turn the can upside down and spray until the valve is clean.

It is strongly recommended that ready for use product is applied at a temperature above 15 °C/59 °F.



Drying

Dust dry (20°C/68 °F) 5 – 10 min

Touch dry (20°C/68 °F) 20 – 30 min

Fully dry (20°C/68 °F) 24 h

Prod. Nr.	Description	Volume	Packaging Box
9008-A-0,5	Anthracite	500 ml	12
9008-B-0,5	Black	500 ml	12

VOC

VOC 2004/42/IIB(e) (840) 820

Shelf life

Min. 24 months from the production date under normal storage conditions and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.